





EU Type Examination Certificate

Date: 2022/08/04

n. 847223102/OE

Validity: 2027/08/03

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

| | | |
|---|---|--|
| Manufacturer: (Responsible of the PPE) | Hase Safety Gloves GmbH Am Hillernsen Hamm, 6 – D-26441 Jever Country – Germany | |
| Type of PPE: | safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials) | |
| Category of PPE: | II : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force. | |
| Model | "SHERPA-85 NU3" Line ST85 REMISBERG | |
| Description: |   <p> <u>model:</u> B (ankle boot); <u>fastening system:</u> by means of laces; <u>processing:</u> direct injection; <u>outsole:</u> transparent grey compact PU marked "antistatic sole oil hydrocarbons resistant 85 remisberg sro passed shock absorber" (ST85 REMISBERG); <u>midsole:</u> black PU foam; <u>outer toetip reinforcement:</u> made of the same material as that of the midsole; <u>upper:</u> - brown greased RUSTIKA Hydro grain leather declared thickness 1.8-2.0 mm (PE FION752); - black coated calf leather PAMPAS declared thickness 2,0-2,2 mm (PE PUK800); <u>collar:</u> - black knitting matched with MTP (TE DALM800); - red Nubuk leather declared thickness 1,4-1,6 mm (PE SCHK500); <u>tongue:</u> - black knitting (TE DAL800), centrally lined and padded; - red Nubuk leather declared thickness 1,4-1,6 mm (PE SCHK500); <u>bellows:</u> black coated fabric (FO CLB801); <u>vamp lining:</u> black three-dimensional fabric "AERPLUS BZBI" (FO RET800) + white non-woven fabric with MTP 3 mm (FO MTP0300); <u>quarter lining:</u> black three-dimensional fabric (FO RET805); <u>heel-grip:</u> black microsuede "Dualmicro" declared thickness 1,1/1,0 mm (FO MCT800); <u>insole:</u> beige non-woven fabric 2,5 mm thick (SO TEX002); <u>penetration resistant insert:</u> inox steel, article "OY 0160 by BTL Steel" (LM 0160); <u>removable insock:</u> cover grey fabric (PA) 120 gr/mq – soft foam PU 3,5 mm (SU ANRE01); <u>toecap:</u> composite reinforced with fiber glass, article "C214 by Contender" (PT C214FG). </p> | |
| Technical Standard: | EN ISO 20344:2011 (UNI EN ISO 20344:2012) EN ISO 20345:2011 (UNI EN ISO 20345:2012) | Personal protective equipment – Test methods for footwear Personal protective equipment – Safety footwear |
| Intended use: | general industry, engineering industry, agriculture, warehouses, works on trucks, cranes. | |
| Size range: | from 36 to 48 | |

